

# Product Sheet

17.05.2024



<b>Description</b>	Circular table saw (400 V)
<b>Model</b>	5543
<b>ID</b>	82154
<b>Length/Width/Height</b>	133/170/95 cm
<b>Weight</b>	150 kg

Dimensions (with arm) 1330/1700/950 mm, power supply 400 V~/50 Hz, motor power output S1 2.2 kW, motor power output S6 3 kW, motor protection, main table size 650/350 mm, table extension 650/270 mm and 350/350 mm, format table 1300/238 mm, outlay table 460/600 mm, table height 830 mm, tilt settings up to 45°, saw blade Ø 250, saw blade bore Ø 30 mm, saw shaft speed 4000 1/min, maximum cutting height at 90° 80 mm and at 45° 54 mm (with saw blade Ø 250 mm), saw blade completely retractable, mitre fence with workpiece clamping +- 60° infinitely adjustable, precision longitudinal fence 650 mm long with fine adjustment for cutting width up to 600 mm, format sliding carriage for cutting length up to 1250 mm, movable outlay table with cross stop, which can be used on both sides infinitely variable from 0 to 45°, 1030 mm long, incl. angle scale and 90° angle stop, weight approx. 150 kg, saw blade guard with intake sockets, central hose connection Ø 100 mm, carbide saw blade, CE-approval, installed ready for operation including initial instruction.

Changes and errors reserved. Illustrations similar.